

HARO

Sports

Datasheet Stockholm 10F

Type: area-elastic sports floor
 Usage: sports- and multi-purpose facilities
 Underfloor heating compatible



1. HARO Premium sports parquet
2. PE-foil
3. Counter floor
4. HARO elastic beam

Structure from top edge of raw concrete	
27 mm	HARO elastic beam module consisting of one springboard layer with spring elements, distance center/center 500 mm laid out in longitudinal direction of hall
17 mm	Counter floor module, distance center/center: 137.5 mm in transverse position fixed to the HARO single swing beam. The spruce modules are kiln-dried, parallel edged, planed on all sides, manufactured in fixed lengths.
0.03 mm	PE-foil, 10 % overlapped, loosely laid out
12.6 mm	HARO Sports parquet modules stapled to counter floor, with precious wood top layer of 3.6 mm and wear-resistant, factory applied PERMADUR® sealant
56.6 mm	Construction height

Model Stockholm 10F entirely meets and exceeds the EN 14904, FIBA rules 2010, DIN V 18032-2; April 2001 standards and is subject to the annual quality control RAL GZ 942. This floor has a general building authority approval.



Hamberger Flooring GmbH & Co. KG
 Rohrdorfer Straße 133, 83071 Stephanskirchen, DE
 Phone +49 8031 700-240, Fax +49 8031 700-249
 email: info@haro-sports.com, web: www.haro-sports.com